

# SKiiP 2414 GB17E4-4DUW V2



SKiiP® 4

## 2-pack-integrated intelligent Power System

### SKiiP 2414 GB17E4-4DUW V2

#### Features\*

- Intelligent Power Module
- Integrated current and temperature measurement
- Integrated DC-link measurement
- Solder free power section
- IGBT4 and CAL4F technology
- Safety isolated switching and sensor signals
- Digital signal transmission
- CAN Interface
- 100% tested IPM
- RoHS compliant
- UL file no. E242581

#### Typical Applications

- Renewable energies
- Traction
- Elevators
- Industrial drives

#### Remarks


For further information please refer to SKiiP@4 Technical Explanation

#### Footnotes

<sup>1)</sup>With assembly of suitable MKP capacitor per terminal


<sup>2)</sup>The specified maximum operation junction temperature  $T_{vjop}$  can be > 150°C for a max. of 1000cum. Operations hours

Absolute Maximum Ratings						
Symbol	Conditions		Values	Unit		
<b>System</b>						
$V_{CC}^{1)}$	Operating DC link voltage		1300	V		
$V_{isol}$	DC, $t = 1$ s, each polarity		5600	V		
$I_{t(RMS)}$	per AC terminal, rms, sinusoidal current		500	A		
$I_{max (peak)}$	max. peak current of power section		3600	A		
$I_{FSM}$	$T_j = 175$ °C, $t_p = 10$ ms, sin 180°		15885	A		
$I^2t$	$T_j = 175$ °C, $t_p = 10$ ms, diode		1262	kA <sup>2</sup> s		
$f_{out}$	fundamental output frequency (sinusoidal)		1	kHz		
$T_{stg}$	storage temperature		-40 ... 85	°C		
<b>IGBT</b>						
$V_{CES}$	$T_j = 25$ °C		1700	V		
$I_C$	$T_j = 175$ °C	$T_s = 25$ °C	3385	A		
		$T_s = 70$ °C	2723	A		
$I_{Cnom}$			2400	A		
$T_j^{2)}$	junction temperature		-40 ... 175	°C		
<b>Diode</b>						
$V_{RRM}$	$T_j = 25$ °C		1700	V		
$I_F$	$T_j = 175$ °C	$T_s = 25$ °C	2362	A		
		$T_s = 70$ °C	1869	A		
$I_{Fnom}$			2400	A		
$T_j^{2)}$	junction temperature		-40 ... 175	°C		
<b>Driver</b>						
$V_s$	power supply		19.2 ... 28.8	V		
$V_{iH}$	input signal voltage (high)		$V_s + 0.3$	V		
$dv/dt$	secondary to primary side		75	kV/μs		
$f_{sw}$	switching frequency		10	kHz		
<b>Characteristics</b>						
Symbol	Conditions		min.	typ.	max.	Unit
<b>IGBT</b>						
$V_{CE(sat)}$	$I_C = 2400$ A at terminal	$T_j = 25$ °C	2.12	2.43	V	
		$T_j = 150$ °C	2.53	2.79	V	
$V_{CE0}$		$T_j = 25$ °C	1.10	1.20	V	
		$T_j = 150$ °C	1.00	1.10	V	
$r_{CE}$	at terminal	$T_j = 25$ °C	0.42	0.51	mΩ	
		$T_j = 150$ °C	0.64	0.70	mΩ	
$E_{on} + E_{off}$	$I_C = 2400$ A	$V_{CC} = 900$ V	1780	mJ		
		$V_{CC} = 1300$ V	2840	mJ		
$R_{th(j-s)}$	per IGBT switch				0.0138	K/W
$R_{th(j-r)}$	per IGBT switch				0.01	K/W



GB

# SKiiP 2414 GB17E4-4DUW V2



SKiiP® 4

## 2-pack-integrated intelligent Power System

### SKiiP 2414 GB17E4-4DUW V2

#### Features\*

- Intelligent Power Module
- Integrated current and temperature measurement
- Integrated DC-link measurement
- Solder free power section
- IGBT4 and CAL4F technology
- Safety isolated switching and sensor signals
- Digital signal transmission
- CAN Interface
- 100% tested IPM
- RoHS compliant
- UL file no. E242581

#### Typical Applications

- Renewable energies
- Traction
- Elevators
- Industrial drives


#### Remarks

For further information please refer to SKiiP@4 Technical Explanation

#### Footnotes

- <sup>1)</sup>With assembly of suitable MKP capacitor per terminal
- <sup>2)</sup>The specified maximum operation junction temperature  $T_{vjop}$  can be  $> 150^{\circ}\text{C}$  for a max. of 1000cum. Operations hours

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
<b>Diode</b>						
$V_F = V_{EC}$	$I_F = 2400\text{ A}$ at terminal	$T_j = 25^{\circ}\text{C}$		2.02	2.34	V
		$T_j = 150^{\circ}\text{C}$		2.27	2.62	V
$V_{F0}$		$T_j = 25^{\circ}\text{C}$		1.21	1.36	V
		$T_j = 150^{\circ}\text{C}$		0.99	1.12	V
$r_F$	at terminal	$T_j = 25^{\circ}\text{C}$		0.34	0.41	m $\Omega$
		$T_j = 150^{\circ}\text{C}$		0.53	0.63	m $\Omega$
$E_{rr}$	$I_F = 2400\text{ A}$ $T_j = 150^{\circ}\text{C}$	$V_R = 900\text{ V}$		412		mJ
		$V_R = 1300\text{ V}$		664		mJ
$R_{th(j-s)}$	per diode switch				0.0281	K/W
$R_{th(j-r)}$	per diode switch				0.0241	K/W
<b>Driver</b>						
$V_s$	supply voltage non stabilized		19.2	24	28.8	V
$I_{SO}$	bias current @ $V_s = 24\text{V}$ , $f_{sw} = 0$ , $I_{AC} = 0$			260		mA
$I_S$	$k_1 = 46\text{ mA/kHz}$ , $k_2 = 0,00015\text{ mA/A}^2$ , $f_{out} = 50\text{Hz}$ , sinusoidal current		$= 260$	$+ k_1 * f_{sw}$	$+ k_2 * I_{AC}^2$	mA
$V_{IT+}$	input threshold voltage (HIGH)		$0,7 * V_s$			V
$V_{IT-}$	input threshold voltage (LOW)				$0,3 * V_s$	V
$R_{IN}$	input resistance			13		k $\Omega$
$C_{IN}$	input capacitance			1		nF
$t_{pRESET}$	error memory reset time			500		ms
$t_{pReset(OCP)}$	Over current reset time, FRT-function can be activated via CAN interface					$\mu\text{s}$
$t_{TD}$	top / bottom switch interlock time			3		$\mu\text{s}$
$t_{jitter}$	jitter clock time			50	58	ns
$t_{SIS}$	short pulse suppression time			0.6		$\mu\text{s}$
$t_{POR}$	Power-On-Reset completed				1	s
$I_{digiout}$	digital output sink current (HALT-signal)				16	mA
$V_{it+ HALT}$	input threshold voltage HIGH HALT (Low -->High)		$0,6 * V_s$			V
$V_{it- HALT}$	input threshold voltage LOW HALT (High --> Low)				$0.4 * V_s$	V
$t_{d(Err)}$	Error delay time (from detection to HALT), (depends on kind of error)		3		370	$\mu\text{s}$
$I_{TRIPSC}$	over current trip level		3600			$A_{PEAK}$
$I_{LL}$				n.a.		$A_{PEAK}$
$T_{trip}$	over temperature trip level		128	135	142	$^{\circ}\text{C}$
$T_{DriverTrip}$	over temperature PCB trip level		113	120	124	$^{\circ}\text{C}$
$V_{DCtrip}$	over voltage trip level,		1300	1340	1380	V
$V_{DCtripLL}$				n.a.		V



GB

# SKiiP 2414 GB17E4-4DUW V2



SKiiP® 4

## 2-pack-integrated intelligent Power System

### SKiiP 2414 GB17E4-4DUW V2

#### Features\*

- Intelligent Power Module
- Integrated current and temperature measurement
- Integrated DC-link measurement
- Solder free power section
- IGBT4 and CAL4F technology
- Safety isolated switching and sensor signals
- Digital signal transmission
- CAN Interface
- 100% tested IPM
- RoHS compliant
- UL file no. E242581

#### Typical Applications

- Renewable energies
- Traction
- Elevators
- Industrial drives

#### Remarks


For further information please refer to SKiiP®4 Technical Explanation

#### Footnotes

<sup>1)</sup>With assembly of suitable MKP capacitor per terminal

<sup>2)</sup>The specified maximum operation junction temperature  $T_{vjop}$  can be  $> 150^{\circ}\text{C}$  for a max. of 1000cum. Operations hours

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
<b>System</b>						
$t_{d(on)IO}$	$V_{CC} = 1300\text{ V}$ $I_C = 2400\text{ A}$	turn on propagation delay time		2.8		$\mu\text{s}$
$t_{d(off)IO}$	$T_j = 25^{\circ}\text{C}$	turn off propagation delay time		2.6		$\mu\text{s}$
$dV_{CE}/dt_{on}$	$T_j = 25^{\circ}\text{C}$ $V_{CC} = 1300\text{ V}$	$I_C = 0\text{ A}$		14		$\text{kV}/\mu\text{s}$
		$I_C = 2400\text{ A}$		3		$\text{kV}/\mu\text{s}$
$dV_{CE}/dt_{off}$		$I_C = 2400\text{ A}$		10		$\text{kV}/\mu\text{s}$
$R_{th(s-a)}$	flow rate = 15 l/min, $T_{Fluid}=40^{\circ}\text{C}$ , water/glycol ratio 50%:50%				0.0065	$\text{K}/\text{W}$
$R_{CC'+EE'}$	measured per switch, $T_s = 25^{\circ}\text{C}$			0.0675		$\text{m}\Omega$
$L_{CE}$	commutation inductance			4.5		$\text{nH}$
$C_{CHC}$	coupling capacitance secondary to heat sink			6		$\text{nF}$
$C_{ps}$	coupling capacitance primary to secondary			0.08		$\text{nF}$
$I_{CES} + I_{RD}$	$V_{GE} = 0\text{ V}$ , $V_{CE} = 1700\text{ V}$ , $T_j = 25^{\circ}\text{C}$			0.199		$\text{mA}$
$M_{dc}$	DC terminals		6		8	$\text{Nm}$
$M_{ac}$	AC terminals		13		15	$\text{Nm}$
w	SKiiP System w/o heat sink			3.22		$\text{kg}$
$w_h$	heat sink			4.25		$\text{kg}$



GB

## Isolation coordination acc. to EN 50178 and IEC 61800-5-1

Maximum grid RMS voltage, line-to-line, grounded delta mains	690V+20%
Installation altitude for maximum grid RMS voltage, line-to-line, grounded delta mains	2000m
Maximum grid RMS voltage, line-to-line, star point grounded mains	690V+20%
Installation altitude for maximum grid RMS voltage, line-to-line, star point grounded mains	4000m
Maximum transient peak voltage between low voltage circuit and mains	1900V
Pollution degree acc. to IEC 60664-1 outside the moulded power section	2
Overvoltage cat. acc. to IEC 60664-1 for mains	III
Overvoltage cat. acc. to UL 840 within mains	I
Overvoltage cat. acc. to UL 840 between mains and ground	III
Overvoltage cat. acc. to UL 840 between mains and low voltage circuit	III
Basic isolation	between heat sink and mains
Reinforced isolation	between low voltage circuit and mains
Protection level acc. to IEC 60529	IP00

## Environmental conditions acc. to IEC 60721

	Storage	Transportation	Operation stationary use at weather protected locations	Operating ground vehicle installations	Operating ship environment
Climatic conditions	1K2 <sub>(1)</sub>	2K2 <sub>(1)</sub>	3K3 <sub>(1)</sub>	5K1 <sub>(1)</sub>	6K1 <sub>(1)</sub>
Biological conditions	1B1	2B1	3B1	5B1	6B1
Chemically active substances (excluded: salt spray)	1C2	2C1	3C2	5C2	6C2
Mechanically active substances	1S1	2S1	3S1	5S1	6S1
Mechanical conditions	1M3	(4)	3M6 <sub>(2)</sub>	5M3 <sub>(3)</sub>	6M3
Contaminating fluids	---	---	---	5F1	---

(1) expanded temperature range: -40°C / +85°C. Please note: by operation near 85°C the life time of product is reduced.

(2) 3M7 possible, but due to the mechanic load capacity of external components like DC-Link capacitors limited to 3M6

(3) 5M3 without impact of foreign bodies, stones

(4) no declaration due to customer-specific packing




Fig. 1: Typical IGBT output characteristics




Fig. 2: Typical diode output characteristics




Fig. 3: Typical switching energy  $E = f(I_C)$




Fig. 4: Typical switching energy  $E = f(I_C)$




Fig. 5: Transient thermal impedance  $Z_{th}(j-s)$




Fig. 6: Transient thermal impedance  $Z_{th}(j-r)$




Fig. 7: Transient thermal impedance  $Z_{th}(s-a)$

	$R_{th} [K/W]$				
	1	2	3	4	5
$Z_{th}(j-s) I$	0,0010	0,0049	0,0055	0,0017	0,0007
$Z_{th}(j-s) D$	0,0020	0,0100	0,0112	0,0034	0,0015
$Z_{th}(j-r) I$	0,0020	0,0048	0,0023	0,0008	
$Z_{th}(j-r) D$	0,0012	0,0039	0,0104	0,0054	0,0032
$Z_{th}(s-a)$	0,0014	0,0050	0,0001		
	$\tau [s]$				
	1	2	3	4	5
$Z_{th}(j-s) I$	3,6500	0,4100	0,0650	0,0090	0,0008
$Z_{th}(j-s) D$	3,6500	0,4100	0,0650	0,0090	0,0008
$Z_{th}(j-r) I$	0,4500	0,0475	0,0142	0,0016	
$Z_{th}(j-r) D$	4,1546	0,2644	0,0497	0,0107	0,0005
$Z_{th}(s-a)$	34,2609	5,2284	0,0005		

Fig. 8: Coefficients of thermal impedances




Fig. 9: Thermal resistance  $R_{th}(s-a)$  versus flow rate  $V$





Fig. 10: Pressure drop  $\Delta p$  versus flow rate  $V$

# SKiP 2414 GB17E4-4DUW V2



All dimensions in mm!

## System

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

### \*IMPORTANT INFORMATION AND WARNINGS

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.